

Perma Core®
Ultimate



POLYESTER
WRAPPED
POLY CORE

World of A&E

www.amefird.com

Perma Core® Ultimate

A&E premium core thread *specifically designed* to help you minimize seam puckering in your no-iron, wrinkle-free seaming applications!



TAILORED CLOTHING APPLICATIONS

- SHIRTING
- SUITS
- NECKWEAR
- EVENING DRESSES
- JACKETS
- OVERCOATS
- SHEER FABRICS

KEY PRODUCT FEATURES

- Lowest shrinkage poly-core thread that helps minimize puckering during finishing and laundering.
- Excellent frictional characteristics allowing **Perma Core® Ultimate** to be sewn with minimum thread tensions.
- Higher tenacity construction allowing smaller thread sizes to be used to minimize yarn displacement puckering on tailored garments (Tex 16, Tex 18 & Tex 24).
- Higher resistance to stretching under normal sewing tensions eliminating tension puckering.
- **Perma Core® Ultimate** has a very smooth thread surface contributing to superior stitch and seam appearance
- Excellent sewability on manual and automatic sewing equipment.

“There is a Difference”



Perma Core®

Ultimate



POLYESTER
WRAPPED
POLY CORE

World of A&E

www.amefird.com

Perma Core® Ultimate

A&E premium core thread *specifically designed* to help you minimize seam puckering in your no-iron, wrinkle-free seaming applications!

Common Causes of Seam Puckering*

- Yarn Displacement during Sewing
- Tension Puckering during Sewing
- Ply Mismatching during Sewing
- Shrinkage during Finishing or Laundering

*See A&E's 'Minimizing Seam Puckering' Technical Bulletins at www.amefird.com.

Perma Core® Ultimate

Thread Sizes	Metric Tex	M180 16	M160 18	M120 24
Strength	cN	825	860	1100
	lb	1.85	1.93	2.47
Hot Air Shrinkage 180 Celsius		0.0%	0.0%	0.0%
Minimum Needle Size- Metric		55	65	70
Minimum Needle Size- Singer		8	10	12
Unit Lengths		5000 Meter Units		

For information or samples, contact your local A&E Representative
 American & Efird Inc
 22 American Street, Mt. Holly, North Carolina 28120
 (800) 438-5868 / Fax: 704-827-0974
 Website: www.amefird.com

